

GREENVILLE UTILITIES COMMISSION

GREENVILLE, NORTH CAROLINA

ADDENDUM (1) FOR #18-43 FOR ONE (1) COMPACT EXCAVATOR

To: All Prospective Proposers and Others Concerned

Subject: Addendum No.1

The intent of this addendum is to notify all prospective proposers and others concerned that the Specifications and Documents are hereby modified as follows:

1. Replace page(s) 5,6 and 7 of 21 with the below.

The foregoing changes shall be incorporated in the Specifications and Documents.

Please acknowledge receipt of this addendum by e-mailing Cleve Haddock, CLGPO, Procurement Coordinator at: haddocgc@guc.com (252) 551-1533

SECTION II

GREENVILLE UTILITIES COMMISSION

MINIMUM SPECIFICATIONS FOR ONE (1) COMPACT EXCAVATOR

AUGUST 9, 2018

It is the intent of these **minimum specifications** to describe a new, current year production model compact excavator. The unit must meet or exceed current OSHA regulations at time of purchase. Any additional equipment or accessories listed in the manufacturer's current literature as standard, but not listed in these minimum specifications, must be furnished.

1.0 Engine: Tier 4 Certified –

3 Cylinder

Displacement – 100 cubic inches or greater.

Fuel Injection – Direct

Fuel Injection Pump – Mechanical or electronic

Fuel - Diesel

Fuel Filter – Full flow, spin on filter

Cooling - Liquid

Horsepower – Net 14-26.5 at 2500 rpm

Max. Torque at 1320 rpm – Net 58.3 lb.-f

2.0 Hydraulics: Two variable-displacement and one fixed-gear pumps, open center design

3.0 Drive: Planetary drive system

Rubber tracks

4.0 Electrical:

Voltage – 12 volts, negative ground

Alternator – 55 amp

Batteries (1) – 12 volt, low maintenance, min. 750 cold crankv

Two (2) work lights, one (1) on work station and one (1) on boom.

5.0 Operating Weight: 6,358 lbs. – 8300 lbs. max

6.0 Performance Specifications:

Max. Dig Radius	-	15 ft
Dig Radius at Groundline	-	14 ft.
Max. Dig Depth	-	10 ft.
Dump Height	-	11 ft..
Overall Reach Height	-	15 ft

Bucket Rotation	-	178 °
Vertical Straight Wall dig Depth	-	8 ft.
Arm Digging Force	-	3,800 lb.
Bucket Digging Force	-	6,500 lb.
Track Overall Width	-	6 ft max

7.0 Operator's Compartment:

Cab with Heat and Air Conditioning

Operator's controls – joystick and foot controls

Display includes – Engine oil pressure, water temperature lamp, air filter lamp, water separator detection lamp, low fuel warning lamp, battery charge lamp, glow plug indicator lamp, water temperature gauge and hour meter

Adjustable seat with seat belt

Arm rests

8.0 Other Equipment: Hydraulic backfill blade & articulating front blade

Width	5 ft.
Buckets –	
Width	- 18 in.
CFT, HD	- 2.9ft.

LINES, BOOM

LINES, STICK

TRACK, RUBBER BELT

BATTERY, DISCONNECT

RADIO

DRAIN, ECOLOGY

BLADE, 70", WELD-ON

SERIALIZED TECHNICAL MEDIA KIT

LINES, QUICK COUPLER (LONG)

MIRROR, CANOPY, LEFT

MIRROR, CAB, REAR

BEACON SOCKET

THUMB HYD/COUPLER HYD

BUCKET, 18", 2.9 CFT, HD

SHIPPING/STORAGE PROTECTION

PACK, DOMESTIC TRUCK

RADIO, READY

9.0 Manuals: Operator and Parts/Repair (2) – must be provided at time of delivery

10.0 Warranty: The entire unit shall have:

Twelve (12) month minimum warranty, parts and labor.

36 Months / 3000 Hour Extended Powertrain + Hydraulic Warranty Included.

All warranty FOB Greenville Utilities Commission, 801 Mumford Rd., Greenville, N.C.
Authorized service center shall be within 50 miles of Greenville, N.C.

Additional Instructions to Bidders

Successful bidder shall be required to furnish Greenville Utilities with a written guaranteed delivery date upon receipt of order.

Completed unit shall be delivered and placed in-service at the Greenville Utilities Operation Center, 801 Mumford Rd., Greenville, North Carolina.

SUBMIT BID ON ATTACHED PROPOSAL FORM(S)

[Balance of page left blank intentionally]