

GREENVILLE UTILITIES COMMISSION

GREENVILLE, NORTH CAROLINA

Q&A's

RFQ 20-61 FOR ONE TELESCOPIC BOOM LIFT 1/6/2021 @ 3:00PM (EDST)

Q: I am quoting the JLG 660SJ and I have a question. You specs are requesting 110 Power in the Platform. This happens two ways. Either you plug in a drop cord at the base of the machine or you have a machine with SkyPower installed. There is a difference in price so I want to make sure I quote the correct unit.

A: If you look at the brochure for this lift, a 110v AC receptacle in the platform is listed as a standard feature.

Standard Features

- Oscillating Axle
- Hydraulic Platform Rotator
- 110VAC Receptacle in the Platform
- 5 Degree Tilt Alarm/Indicator Light
- Swing-Out Engine Tray
- 12V DC Auxiliary Power
- Hourmeter
- SkyGuard SkyLine™
- Control ADE® System
- All Motion Alarm
- Proportional Controls
- Gull-Wing Hoods
- Platform Console Machine Status
- Light Panel*
- Engine Distress Warning/Shutdown—
- Selectable via JLG Analyzer
- Lifting/Tie Down Lugs
- Load Sensing System

*Provides indicator lights at platform control console for system distress, fuel level, low fuel, 5 degree tilt light and foot switch status.