

GREENVILLE UTILITIES COMMISSION
GREENVILLE, NORTH CAROLINA
ONE (1) 4-WHEEL DRIVE QUAD TRACK, FRONT AND REAR
STEER, BACKHOE, PLOWING MACHINE WITH BACKFILL BLADE

To: All Prospective Proposers and Others Concerned

Subject: Addendum No.1

The intent of this addendum is to notify all prospective proposers and others concerned that the Specifications and Documents are hereby modified as follows:

1. Replace page(s) 5, with the enclosed page(s).

The foregoing changes shall be incorporated in the Specifications and Documents.

Please acknowledge receipt of this addendum by e-mailing Cleve Haddock, Purchasing Technician at (252) 551-1533, haddocgc@guc.com.

SECTION II

GREENVILLE UTILITIES COMMISSION

MINIMUM SPECIFICATIONS FOR ONE (1) 4-WHEEL DRIVE QUAD

**TRACK, FRONT AND REAR STEER, BACKHOE, PLOWING MACHINE WITH
BACKFILL**

BLADE

SEPTEMBER 27, 2012

It is the intent of these specifications to describe a 74 gross HP (minimum), new current production model, hydrostatic 4-Wheel Drive, quad track, Front and rear steering Backhoe Plowing Machine, with a backfill blade. Any additional equipment or accessories listed in the manufacturer's current literature as standard, but not listed in these specifications, must be furnished. The unit must meet or exceed current OSHA regulations at the time of purchase. The unit must meet the following minimum specifications:

Engine: Minimum 74 Gross Horsepower
Cooling System – Liquid
4 Cylinder – turbo diesel, must meet Tier III emissions standards

Ground Drive: Hydrostatic

Wheelbase: 60" minimum

Differential: Front and rear heavy duty steerable planetary axles with differential lock

Tracks: Must have quad rubber track system.

Front Steering: Power, conventional automotive type steering.

Rear Steering: Unit must have power/hydraulic rear steering.

Vibratory Plow Data: Plow must be of heavy/severe duty type.

Digging Depth – 36" minimum

Pulling- Must be capable of pulling 4" polyethylene pipe

Plow Blade- Must be capable of swinging at least 30 degrees left and right while in operation

Cover Depth- Must have at least 36" ground coverage over pipe

Shaker force- 24,000 lbs. minimum

Additional plow blade capable of feeding 1" roll pipe with 36" cover.